

# KP3868-30

## CONTINUOUS FORM LASER PRINTER



Printing speed up to 3000 LPM(6LPI) / 59 PPM (8.5" length) with 300 x 300 dpi / 600 x 600 dpi quality  
Paper width from 6 to 18 inches  
Maximum 17-inch print width  
First page printable without waste of paper  
Flat paper path ideal for label printing  
Effective paper loading and splitting  
Automatic paper stacking without user intervention  
Well-suited for 1D & 2D bar code (QR Code, PDF 417), and optical character printing



### EXCELLENT PERFORMANCE

**KP3868-30** printer has an excellent performance of printing up to 3000 lines per minute with 300 or 600 dpi resolution. Printing images and graphics is certainly at full speed. The robust print engine and hardware give the printer the power to have a duty cycle of 600,000 pages (8.5" length) per month.

### SUPERB PAPER HANDLING

**KP3868-30** printer offers a printable width of maximum 17 inch, with first page printable to minimize the waste of paper. Its automatic paper loading mechanism can reliably feed fanfold paper 6 to 18-inch wide. The companioned Power Stacker, with a capacity of 3,000 sheets, automatically stacks paper output without user intervention. The auto-splitter provides the benefit of splitting paper output automatically instead of manually, which is a great alternative to enhance productivity.

### FLAT PAPER PATH

**KP3868-30** printer employs flat paper path that transports paper straightly without turns. This paper transport mechanism greatly reduces paper jams, and is particularly ideal for label printing since labels don't get peeled off on internal rollers.

### EASY OPERATION

**KP3868-30** printer is easy to operate. The LCD operation panel provides an easy configuration interface for users. All features are designed to offer you a friendly printing environment.

**KPOWER**

**KP3868-30 SPECIFICATIONS**

Printing Method		Electrophotography process, LED array
Developing Method		Dry, two-ingredient developer
Fusing		Xenon flash fusing system
Printing Speed		3000 LPM (6LPI), 59 PPM (8.5" length)
Resolution		300 x 300 DPI / 600 x 600 DPI
Monthly Duty Cycle		600K pages (8.5" length)
Lifetime		5 years or 48,000,000 pages (8.5" length)
Printable Width		17 inches Max.
Paper	Type	Fanfold continuous paper
	Weight	64 to 204 g/m <sup>2</sup>
	Width	6 to 18 inches
	Length	7 to 20 inches
Paper Hopper/Stacker Capacity		3000 sheets (64 g/m <sup>2</sup> )
Power Requirement	Voltage	AC 200 – 230 V
	Frequency	50 Hz / 60 Hz
	Phase	Single phase, three wires (one for FG)
Power Consumption		Operating: 3.7 KW (Max.), Standby: 0.6 KW (Max.)
Environment	Temperature	Operating: 15°C to 30°C
	Humidity	30% to 80% (RH) (NON-CONDENSING)
Operation Panel		LCD panel
Dimensions		780 mm (W) x 1320 mm (H) x 890 mm (D) 780 mm (W) x 1320 mm (H) x 1520 mm (D) with stacker
Weight		255 KG (562 lbs.), 300 KG (661 lbs.) with stacker

Specifications are subject to change without notice.

All brand names or registered trademarks are the property of their respective owners.



**KPOWERSCIENCE CO., LTD.**  
**ISO 9001 Certified**

**KPOWER**

**CHINESE BUSINESS DEPARTMENT**

8FL., NO. 276, SEC. 1, TA-TUNG RD.,  
HSI-CHIH DIST., NEW TAIPEI CITY 22146, TAIWAN  
TEL: +886-2-2647-5855 FAX: +886-2-2643-1151  
E-MAIL: leann@kpower.com.tw

**INTERNATIONAL BUSINESS DEPARTMENT**

8FL., NO. 276, SEC. 1, TA-TUNG RD.,  
HSI-CHIH DIST., NEW TAIPEI CITY 22146, TAIWAN  
TEL: +886-2-2647-5855 FAX: +886-2-2643-1151  
E-MAIL: stevenlin@kpower.com.tw